



# 4045

LOCKING CLIP



## IMPORTANT INFO


- Use if vehicle's lap/shoulder belt latch plate slides freely. A locking clip will prevent movement.
- Do not use locking clip to shorten seat belt.
- Remove locking clip from seat belts when not being used with child restraint.

## WARRANTY

EZ-ON Products stands behind the products we make. Warranty covers any defects in material or workmanship under normal use during the warranty period. We will repair or replace product defects for 1 year from manufacturer date.

## WARNING

Death or serious injury can occur if manufacturer's instructions are not followed correctly. All EZ-ON products are dynamically tested to meet NHTSA standards. Please follow washing instructions on product tag. Replace product if it is damaged, frayed, or has been in a crash. Recommended replacement after six years. EZ-ON Products are not liable for injury if these recommendations are not followed.



## INSTALLATION INSTRUCTIONS

1. Install child restraint and tighten vehicle seat belt.
2. Hold seat belts together at latch plate.
3. Un-buckle seat belt.
4. Slide locking clip on seat belt approximately  $\frac{1}{2}$  inch away from latch plate.
5. Re-buckle seat belt.

\*Test installation to see if the child restraint is secure. If not secure, repeat above steps until secure.

\*If not, secure additional belt tightening may be required.